



dLuxo Statuario / dLuxo Ornament




Rectificado
Wall Tiles

30x60 cm
Glossy


V3




dLuxo



W63435R
dLuxo Statuario
30x60 - Gol. B



W63835R
dLuxo Ornament
30x60 - Gol. C




33435RP
dLuxo Statuario
30x30 - Gol. B

Recommended glossy
flooring with protection
(slip resistant surface)

Shade Variations




Shade variations are the characteristic of the tile that deliberate and visible differences in graphics and colour hue. Digital Tecnica technology creates stunning ceramic tiles with hyper-realistic surface tones, markings and textures which mimic a range of natural materials including; stone, timber, terracotta, cement, mosaic, marble and more.



V1 (Uniform Appearance)
Differences among pieces from the same production run are minimal.

Austin White
50x50




V2 (Slight Variation)
Clearly distinguishable differences in texture and/or pattern within similar colors.

dCervino Bone
50x50



V3 (Moderate Variation)
Amount and intensity of colors on each piece may vary significantly.

dTimber Brown
50x50





V4 (Substantial Variation)
Random color differences each tile, so that one tile may have totally different colors from other tiles.

dBudapest Vintage
50x50

Technical Specification



TECHNICAL CHARACTERISTIC	TEST METHOD OR AS PER NORM	FLOOR TILE		WALL TILE	
		ISO 13006 REQUIREMENT		ISO 13006 REQUIREMENT	
Length and Width	ISO 10545 - 2	± 0.6 %	± 0.4 %	± 0.5 %	± 0.4 %
Side Straightness	ISO 10545 - 2	± 0.5 %	± 0.3 %	± 0.3 %	± 0.3 %
Rectangularity	ISO 10545 - 2	± 0.6 %	± 0.4 %	± 0.5 %	± 0.4 %
Center Curvature & Edge Curvature	ISO 10545 - 2	± 0.5 %	- 0.15 % to + 0.25 %	- 0.3 % to + 0.5 %	- 0.15 % to + 0.25 %
Warpage	ISO 10545 - 2	± 0.5 %	± 0.3 %	± 0.5 %	± 0.3 %
Thickness	ISO 10545 - 2	± 5.0 %	± 4.0 %	± 10 %	± 3.0 %
Water Absorption	ISO 10545 - 3	B1b ≤ 3.0 %	B1 < 3.0 %	B3 > 10 %	B3 Less than 18 %
Modulus of Rupture	ISO 10545 - 4	B1b 30 Ind. Min. 27N/mm ²	≥ 35 N/mm ²	≥ 15 N/mm ²	≥ 17 N/mm ²
Crazing Resistance	ISO 10545 -11	Required	Resistant	Required	Resistant
Chemical Resistance	ISO 10545 - 13	Minimum Class GB	Minimum Class GB	Minimum Class GB	Minimum Class GB
Stain Resistance	ISO 10545 - 14	Minimum Class 3	Minimum Class 4	Minimum Class 3	Minimum Class 5
Abrasion Resistance	ISO 10545 - 7	Group I to V	Group III to V	Not Required	Not Required

NOTE :

- The governing sizes and weights are subject to the usual variations expected of fired ceramic productions.
- Slight variations of shades/colours and surface finishes are inherent due to the nature of ceramic tile production process.